

Ordering Information

Catalog No.	Finish	Mounting	Lamps	Reflectors
23S70T6AL **23S70T6BK** **23S70T6WH**	Aluminum Black White	For use with Lytespan Radius, Basic and Advent Track. Not compatible with extension wands or slope ceiling adapters. For monopoint applications refer to spec sheet 6173.	70W T6 G12 Base Ceramic Metal Halide	MHT6RS, MHT6RNF, MHT6RF MHT6RSCCZ, MHT6RNFCCZ, MHT6RFCCZ REFLECTORS SOLD SEPARATELY

Features

1. **Track Attachment Fitting:** Locking lever for mechanical/ electrical connection.
2. **Brass Contact:** Extends for connection to second circuit (Advent track only).
3. **Horizontal Pivot:** Wireless stem profile with 365° horizontal rotation. Position may be locked using an allen key.
4. **Vertical Pivot:** 0-90° vertical adjustment with aiming indicator. Position may be locked using an allen key.
5. **Fixture Housing:** Die cast aluminum
6. **Ballast Housing:** Die cast aluminum
7. **Safety Lens:** Tempered 1/8" glass. Meets or exceeds UL safety requirement for metal halide lamps.
8. **On/Off Switch:** Rocker switch to disconnect power to the ballast.
9. **Accessory Cartridge:** Hinged and captive; retaining ring included. Inside painted black to reduce glare.
10. **Safety Locking Lever:** Locks ballast housing to track.

Finish

All Painted finishes are baked enamel.

Accessories

Accessory Holder: Integral
Accessories: Accepts 1 snoot plus 2 lenses or 1 louver plus 1 lens. When using 2 accessories, remove safety lens provided.
Lens: AF4, ADF4 Series
Louver: AL4HC

Reflector

Interchangeable reflectors available to allow for desired beam spread. REFLECTORS SOLD SEPARATELY.

Electrical

Electronic Ballast
Input Voltage: 120V, 50/60Hz
Power Factor: High
Input Power: 77W
Max. Input Current: 0.64A
ANSI Code: M139, M98
Do not use on dimming circuit.

Labels

UL, cUL

Job Information **Type:**

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
www.lightolier.com © 2008 Philips Group • B0708

Aiming Angle:

L Beam length
W Beam Width
C Distance to center beam
D Distance
A Aiming Angle
FC Footcandles

L and **W** are the outer points where the candle power drops to 50% of the maximum. **FC** are the initial footcandles at the center of the beam.

Lamp data shown is typical. Consult lamp manufacturers for availability and performance.

CBCP = Center Beam Candle Power.



Lamp	Beam Spread (To 50% CBCP)	CBCP	Rated Life (Hrs.)	0° D	0° FC	0° L	0° W	30° Horizontal D	30° Horizontal C	30° Horizontal FC	30° Horizontal L	30° Horizontal W	30° Vertical D	30° Vertical C	30° Vertical FC	30° Vertical L	30° Vertical W	45° Vertical D	45° Vertical C	45° Vertical FC	45° Vertical L	45° Vertical W
23S70T6-MHT6RS	14°	34129	12000	14'	174	3.4'	3.4'	12'	6.9'	154	3.9'	3.4'	4'	6.9'	267	4.1'	2.0'	6'	6.0'	335	3.0'	2.1'
				16'	133	3.9'	3.9'	14'	8.1'	113	4.6'	4.0'	5'	8.7'	171	5.1'	2.5'	7'	7.0'	246	3.5'	2.4'
				18'	105	4.4'	4.4'	16'	9.2'	87	5.3'	4.5'	6'	10.4'	119	6.2'	2.9'	8'	8.0'	189	4.0'	2.8'
				20'	85	4.9'	4.9'	18'	10.4'	68	5.9'	5.1'	7'	12.1'	87	7.2'	3.4'	9'	9.0'	149	4.5'	3.1'
Lamp	Beam Spread (To 50% CBCP)	CBCP	Rated Life (Hrs.)	**D**	**FC**	**L**	**W**	**D**	**C**	**FC**	**L**	**W**	**D**	**C**	**FC**	**L**	**W**	**D**	**C**	**FC**	**L**	**W**
23S70T6-MHT6RNF	20°	19824	12000	12'	138	4.2'	4.2'	12'	6.9'	89	5.7'	4.9'	4'	6.9'	155	6.2'	2.8'	6'	6.0'	195	4.4'	3.0'
				14'	101	4.9'	4.9'	14'	8.1'	66	6.7'	5.7'	5'	8.7'	99	7.8'	3.5'	7'	7.0'	143	5.1'	3.5'
				16'	77	5.6'	5.6'	16'	9.2'	50	7.6'	6.5'	6'	10.4'	69	9.3'	4.2'	8'	8.0'	110	5.8'	4.0'
				18'	61	6.3'	6.3'	18'	10.4'	40	8.6'	7.3'	7'	12.1'	51	10.9'	4.9'	9'	9.0'	87	6.6'	4.5'
Lamp	Beam Spread (To 50% CBCP)	CBCP	Rated Life (Hrs.)	**D**	**FC**	**L**	**W**	**D**	**C**	**FC**	**L**	**W**	**D**	**C**	**FC**	**L**	**W**	**D**	**C**	**FC**	**L**	**W**
23S70T6-MHT6RF	29°	8893	12000	8'	139	4.1'	4.1'	8'	4.6'	90	5.6'	4.8'	3'	5.2'	124	7.8'	3.1'	3'	3.0'	349	3.3'	2.2'
				10'	89	5.2'	5.2'	10'	5.8'	58	7.1'	6.0'	4'	6.9'	69	10.4'	4.1'	4'	4.0'	197	4.4'	2.9'
				12'	62	6.2'	6.2'	12'	6.9'	40	8.5'	7.2'	5'	8.7'	44	12.9'	5.2'	5'	5.0'	126	5.5'	3.7'
				14'	45	7.2'	7.2'	14'	8.1'	29	9.9'	8.4'	6'	10.4'	31	15.5'	6.2'	6'	6.0'	87	6.7'	4.4'

Note: For Champagne Bronze (CCZ), multiply FC values by 0.64. CCZ Champagne Bronze reflector "warms" the beam to 2700K.

Job Information **Type:**

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
www.lightolier.com © 2008 Philips Group • B0708